# **SAFETY DATA SHEET**



### Section 1. Identification

GHS product identifier	: CITGO Premium Gear Oil (MP), SAE 80W-90
Synonyms	: Gear oil
Material uses	: Gear Oil
Code	: 631310001

Relevant identified uses of the substance or mixture and uses advised against Not applicable.

Supplier's details	: CITGO Petroleum Corporation P.O. Box 4689 Houston, TX 77210 sdsvend@citgo.com
Emergency telephone number (with hours of operation)	: Technical Contact: (800) 248-4684 Medical Emergency: (832) 486-4700 CHEMTREC Emergency: (800) 424-9300 (United States Only)

# Section 2. Hazards identification

OSHA/HCS status	: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
Classification of the substance or mixture	: Not classified.
GHS label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statements	
General	: Keep out of reach of children.
Prevention	: Do not get in eyes, on skin, or on clothing.
Response	: Wash with plenty of soap and water or use a recognized skin cleanser.
Storage	: Store in accordance with all local, regional, national and international regulations. Store in a dry place and a closed container. Empty containers may contain material residues which can ignite with explosive force. Misuse of empty containers can be dangerous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers can cause fire, explosion, or release of toxic fumes from residues. Do not pressurize or expose empty containers to open flame, sparks, or heat. Keep container closed and drum bungs in place. All label warnings and precautions must be observed. Return empty drums to a qualified reconditioner. Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling, or disposing of empty containers and/or waste residues of this material.
Disposal	<ul> <li>Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> </ul>
Hazards not otherwise classified	: None known.

### Section 3. Composition/information on ingredients

#### Substance/mixture Other means of identification

: Mixture : Gear oil

### **CAS number/other identifiers**

CAS number

: Not applicable.

Ingredient name	%	CAS number
	≥25 - ≤50	64742-54-7 64742-62-7 64742-52-5

\* = Various \*\* = Mixture \*\*\* = Proprietary

Any concentration shown as a range is to protect confidentiality or is due to process variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

### Description of necessary first aid measures

Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	<ul> <li>Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.</li> </ul>
Ingestion	: Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

#### Most important symptoms/effects, acute and delayed

Potential acute health effe		
Eye contact	o known significant effects or critical hazards.	
Inhalation	o known significant effects or critical hazards.	
Skin contact	o known significant effects or critical hazards.	
Ingestion	o known significant effects or critical hazards.	
Over-exposure signs/sym		
Eye contact	o specific data.	
Inhalation	o specific data.	
Skin contact	o specific data.	
Ingestion	o specific data.	
Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	reat symptomatically. Contact poison treatment specialist immediately if large uantities have been ingested or inhaled.	
Specific treatments	reat symptomatically and supportively.	
Protection of first-aiders	o action shall be taken involving any personal risk or without suitable training.	

### See toxicological information (Section 11)

### Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

Personal precautions, protec	tive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.	
	Bulk Storage Conditions: Maintain all storage tanks in accordance with applicable regulations. Use necessary controls to monitor tank inventories. Inspect all storage tanks on a periodic basis. Test tanks and associated piping for tightness. Maintain the automatic leak detection devices to assure proper working condition.	

# Section 8. Exposure controls/personal protection

Control parameters		
Occupational exposure limits		
Distillates (petroleum), hydrotre	eated heavy paraffinic	ACGIH TLV (United States, 1/2021). TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction OSHA PEL (United States, 5/2018). TWA: 5 mg/m <sup>3</sup> 8 hours. NIOSH REL (United States, 10/2020). TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist
Residual oils (petroleum), solve	ent-dewaxed	ACGIH TLV (United States, 6/2013). TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction NIOSH REL (United States, 4/2013). TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist OSHA PEL (United States, 2/2013). TWA: 5 mg/m <sup>3</sup> 8 hours.
Distillates (petroleum), hydrotre	eated heavy naphthenic	<ul> <li>ACGIH TLV (United States, 1/2021). TWA: 5 mg/m<sup>3</sup> 8 hours. Form: Inhalable fraction</li> <li>OSHA PEL (United States, 5/2018). TWA: 5 mg/m<sup>3</sup> 8 hours.</li> <li>NIOSH REL (United States, 10/2020). TWA: 5 mg/m<sup>3</sup> 10 hours. Form: Mist STEL: 10 mg/m<sup>3</sup> 15 minutes. Form: Mist</li> </ul>
Appropriate engineering controls	Good general ventilation should b contaminants.	e sufficient to control worker exposure to airborne
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, vapor controls, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	
Individual protection measures	5	
	<ul> <li>Wash hands, forearms and face t eating, smoking and using the lav Appropriate techniques should be</li> </ul>	horoughly after handling chemical products, before atory and at the end of the working period. used to remove potentially contaminated clothing. re reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

# Section 8. Exposure controls/personal protection

Eye/face protection	: Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Avoid skin contact with liquid. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Leather boots are not protective for liquid contact.
Respiratory protection	: Avoid inhalation of gases, vapors, mists or dusts. Use a properly fitted, air-purifying or supplied-air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

### Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Physical state: Liquid.Color: Light amberOdor: Petroleum.pH: Not available.Boiling point, initial boiling point, and boiling range: Not available.Flash point: Open cup: 230°C (446°F) [Cleveland.]Evaporation rate: <1 (n-butyl acetate. = 1)Lower and upper explosive (flammable) limits: Lower: 1% Upper: 7%Vapor pressure: <0.0013 kPa (<0.01 mm Hg)Relative vapor density: >1 [Air = 1]Relative density: 0.887Density Ibs/gal: Estimated 7.39 Ibs/galDensity gm/cm³: Not available.Gravity, °API: Estimated 28 @ 60 FSolubility: Insoluble in the following materials: cold water and hot water.Auto-ignition temperature: $400°C (752°F)$ Viscosity: Kinematic (40°C (104°F)): 139 mm²/s (139 cSt)Viscosity SUS: Estimated 644 SUS @104 FFlow time (ISO 2431): Not available.Particle characteristics: Not applicable.	Appearance		
Odor: Petroleum.pH: Not available.Boiling point, initial boiling point, and boiling range: Not available.Flash point: Open cup: 230°C (446°F) [Cleveland.]Evaporation rate: <1 (n-butyl acetate. = 1)Lower and upper explosive (flammable) limits: Lower: 1% Upper: 7%Vapor pressure: <0.0013 kPa (<0.01 mm Hg)Relative density: >1 [Air = 1]Relative density: 0.887Density lbs/gal: Estimated 7.39 lbs/galDensity gm/cm³: Not available.Gravity, °API: Estimated 28 @ 60 FSolubility: Insoluble in the following materials: cold water and hot water.Auto-ignition temperature: 400°C (752°F)Viscosity SUS: Estimated 644 SUS @104 FFlow time (ISO 2431): Not available.Particle characteristics: Not available.	Physical state	Liquid.	
pH: Not available.Boiling point, initial boiling point, and boiling range: Not available.Flash point: Open cup: 230°C (446°F) [Cleveland.]Evaporation rate: <1 (n-butyl acetate. = 1)Lower and upper explosive (flammable) limits: Lower: 1% Upper: 7%Vapor pressure: <0.0013 kPa (<0.01 mm Hg)Relative vapor density: >1 [Air = 1]Relative density: 0.887Density lbs/gal: Estimated 7.39 lbs/galDensity gm/cm³: Not available.Gravity, °API: Estimated 28 @ 60 FSolubility: Insoluble in the following materials: cold water and hot water.Auto-ignition temperature: 400°C (752°F)Viscosity: Estimated 644 SUS @104 FFlow time (ISO 2431): Not available.Particle characteristics	Color	Light amber	
Boiling point, initial boiling point, and boiling range: Not available.Flash point: Open cup: 230°C (446°F) [Cleveland.]Evaporation rate: <1 (n-butyl acetate. = 1)Lower and upper explosive (flammable) limits: Lower: 1% Upper: 7%Vapor pressure: <0.0013 kPa (<0.01 mm Hg)Relative vapor density: >1 [Air = 1]Relative density: 0.887Density Ibs/gal: Estimated 7.39 lbs/galDensity gm/cm³: Not available.Gravity, °API: Estimated 28 @ 60 FSolubility: Insoluble in the following materials: cold water and hot water.Auto-ignition temperature: 400°C (752°F)Viscosity: Estimated 644 SUS @104 FFlow time (ISO 2431): Not available.Particle characteristics:	Odor	Petroleum.	
point, and boiling rangeFlash point: Open cup: 230°C (446°F) [Cleveland.]Evaporation rate: <1 (n-butyl acetate. = 1)Lower and upper explosive (flammable) limits: Lower: 1% Upper: 7%Vapor pressure: <0.0013 kPa (<0.01 mm Hg)Relative vapor density: >1 [Air = 1]Relative density: 0.887Density Ibs/gal: Estimated 7.39 lbs/galDensity gm/cm³: Not available.Gravity, °API: Estimated 28 @ 60 FSolubility: Insoluble in the following materials: cold water and hot water.Auto-ignition temperature: 400°C (752°F)Viscosity SUS: Estimated 644 SUS @104 FFlow time (ISO 2431): Not available.Particle characteristics: Not available.	рН	Not available.	
Evaporation rate:<1 (n-butyl acetate. = 1)		Not available.	
Lower and upper explosive (flammable) limits: Lower: 1% Upper: 7%Vapor pressure Relative vapor density Relative density Density lbs/gal: <0.0013 kPa (<0.01 mm Hg) : >1 [Air = 1]Relative density Density lbs/gal: <0.887 Estimated 7.39 lbs/galDensity gm/cm³ Gravity, °API Solubility: Estimated 28 @ 60 F : Estimated 28 @ 60 F : Lower (752°F)Viscosity Viscosity Viscosity SUS Flow time (ISO 2431): Kinematic (40°C (104°F)): 139 mm²/s (139 cSt)Particle characteristics: Not available.	Flash point	Open cup: 230°C (446°F) [Cleveland.]	
(flammable) limitsUpper: 7%Vapor pressure:<0.0013 kPa (<0.01 mm Hg)Relative vapor density:>1 [Air = 1]Relative density:0.887Density lbs/gal:Estimated 7.39 lbs/galDensity gm/cm³:Not available.Gravity, °API:Estimated 28 @ 60 FSolubility:Insoluble in the following materials: cold water and hot water.Auto-ignition temperature:400°C (752°F)Viscosity:Estimated 644 SUS @104 FFlow time (ISO 2431):Not available.Particle characteristics:Not available.	Evaporation rate	<1 (n-butyl acetate. = 1)	
Relative vapor density: >1 [Air = 1]Relative density: 0.887Density lbs/gal: Estimated 7.39 lbs/galDensity gm/cm³: Not available.Gravity, °API: Estimated 28 @ 60 FSolubility: Insoluble in the following materials: cold water and hot water.Auto-ignition temperature: 400°C (752°F)Viscosity: Kinematic (40°C (104°F)): 139 mm²/s (139 cSt)Viscosity SUS: Estimated 644 SUS @104 FFlow time (ISO 2431): Not available.			
Relative density: 0.887Density lbs/gal: Estimated 7.39 lbs/galDensity gm/cm³: Not available.Gravity, °API: Estimated 28 @ 60 FSolubility: Insoluble in the following materials: cold water and hot water.Auto-ignition temperature: 400°C (752°F)Viscosity: Kinematic (40°C (104°F)): 139 mm²/s (139 cSt)Viscosity SUS: Estimated 644 SUS @104 FFlow time (ISO 2431): Not available.Particle characteristics	Vapor pressure	<0.0013 kPa (<0.01 mm Hg)	
Density Ibs/gal: Estimated 7.39 Ibs/galDensity gm/cm³: Not available.Gravity, °API: Estimated 28 @ 60 FSolubility: Insoluble in the following materials: cold water and hot water.Auto-ignition temperature: 400°C (752°F)Viscosity: Kinematic (40°C (104°F)): 139 mm²/s (139 cSt)Viscosity SUS: Estimated 644 SUS @104 FFlow time (ISO 2431): Not available.Particle characteristics	Relative vapor density	>1 [Air = 1]	
Density gm/cm³: Not available.Gravity, °API: Estimated 28 @ 60 FSolubility: Insoluble in the following materials: cold water and hot water.Auto-ignition temperature: 400°C (752°F)Viscosity: Kinematic (40°C (104°F)): 139 mm²/s (139 cSt)Viscosity SUS: Estimated 644 SUS @104 FFlow time (ISO 2431): Not available.Particle characteristics	Relative density	0.887	
Gravity, °API: Estimated 28 @ 60 FSolubility: Insoluble in the following materials: cold water and hot water.Auto-ignition temperature: 400°C (752°F)Viscosity: Kinematic (40°C (104°F)): 139 mm²/s (139 cSt)Viscosity SUS: Estimated 644 SUS @104 FFlow time (ISO 2431): Not available.Particle characteristics	Density Ibs/gal	Estimated 7.39 lbs/gal	
Solubility: Insoluble in the following materials: cold water and hot water.Auto-ignition temperature: 400°C (752°F)Viscosity: Kinematic (40°C (104°F)): 139 mm²/s (139 cSt)Viscosity SUS: Estimated 644 SUS @104 FFlow time (ISO 2431): Not available.Particle characteristics	Density gm/cm <sup>3</sup>	Not available.	
Auto-ignition temperature: 400°C (752°F)Viscosity: Kinematic (40°C (104°F)): 139 mm²/s (139 cSt)Viscosity SUS: Estimated 644 SUS @104 FFlow time (ISO 2431): Not available.Particle characteristics	Gravity, °API	Estimated 28 @ 60 F	
Viscosity: Kinematic (40°C (104°F)): 139 mm²/s (139 cSt)Viscosity SUS: Estimated 644 SUS @104 FFlow time (ISO 2431): Not available.Particle characteristics	Solubility	Insoluble in the following materials: cold water and hot water	
Viscosity SUS       : Estimated 644 SUS @104 F         Flow time (ISO 2431)       : Not available.         Particle characteristics	Auto-ignition temperature	400°C (752°F)	
Flow time (ISO 2431)       : Not available.         Particle characteristics	Viscosity	Kinematic (40°C (104°F)): 139 mm²/s (139 cSt)	
Particle characteristics	Viscosity SUS	Estimated 644 SUS @104 F	
	Flow time (ISO 2431)	Not available.	
Median particle size : Not applicable.	Particle characteristics		
	Median particle size	Not applicable.	

### Section 10. Stability and reactivity

Reactivity	: Not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS Definition(s).
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Section 11. Toxicological information

### Information on toxicological effects

Acu	te	tox	ic	itv
Acu		<b>IU</b> A		Ly

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), hydrotreated heavy paraffinic	LD50 Dermal	Rat	>5000 mg/kg	-
Distillates (petroleum), hydrotreated heavy	LD50 Oral LD50 Oral	Rat Rat	>5000 mg/kg >5000 mg/kg	-
naphthenic	LD50 Oral	Rat	>5000 mg/kg	-

Conclusion/Summary
 Distillates (petroleum), hydrotreated heavy paraffinic: Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place exposure levels produced no significant toxicological effects. Distillates (petroleum), hydrotreated heavy naphthenic: Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place exposure levels produced no significant toxicological effects.

### Irritation/Corrosion

Not available.

Skin	: No additional information.
Eyes	: No additional information.
Respiratory	: No additional information.
Sensitization	
Not available.	
Skin	: No additional information.
Respiratory	: No additional information.
Mutagenicity	
Not available.	
Conclusion/Summary	: No additional information.

```
Date of issue/Date of revision : 10/6/2022
```

21

# Section 11. Toxicological information

Carcinogenicity	
Not available.	
Conclusion/Summary <u>Reproductive toxicity</u> Not available.	: No additional information.
Conclusion/Summary <u>Teratogenicity</u> Not available.	: No additional information.
Conclusion/Summary	: No additional information.
Specific target organ toxici Not available.	<u>ty (single exposure)</u>
Specific target organ toxici Not available.	t <u>y (repeated exposure)</u>
Aspiration hazard Not available.	
nformation on the likely routes of exposure	: Routes of entry anticipated: Dermal.
Potential acute health effects	<u>s</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the phy	vsical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate effect	cts and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Date of issue/Date of revision	: 10/6/2022 Date of provious issue : 11/18/2021

# Section 11. Toxicological information

#### Numerical measures of toxicity

Acute toxicity estimates

N/A

### Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated heavy naphthenic	Acute EC50 >10000 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 >100 mg/l Fresh water Acute NOEL >100 mg/l Fresh water	Fish - Pimephales promelas Algae - Pseudokirchneriella subcapitata	96 hours 72 hours
Conclusion/Summary	: Not available.		

### Persistence and degradability

Conclusion/Summary	: Not available.		
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Distillates (petroleum), hydrotreated heavy naphthenic	-	-	Inherent

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Distillates (petroleum), hydrotreated heavy naphthenic	>6	-	high

#### Mobility in soil

Other adverse effects

Soil/water partition: Not available.coefficient (Koc)

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# Section 14. Transport information

	DOT Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

**Oil:** The product(s) represented by this SDS is (are) regulated as "oil" under 49 CFR Part 130. Shipments by rail or highway in packaging having a capacity of 3500 gallons or more or in a quantity greater 42,000 gallons are subject to these requirements. In addition, mixtures containing 10% or more of this product may be subject to these requirements.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

### Section 15. Regulatory information

U.S. Federal regulations		States inventory (TSCA 8	•		
		Nater Act (CWA) 307: ethyl	•		
		Nater Act (CWA) 311: xyler	•		NA/A)
	and the sheen o	aterial is classified as an oil Oil Pollution Act of 1990 (C on waters of the United State ice waters must be reported 02.	PA). Discharges or es, their adjoining sh	spills which produce a v orelines, or into conduits	isible leading
SARA 302/304					
Composition/informatio	<u>n on ingredien</u>	<u>its</u>			
SARA 304 RQ	: Not appli	cable.			
<u>SARA 311/312</u>					
Classification	: Not appli	icable.			
Composition/informatio	<u>n on ingredien</u>	<u>its</u>			
No products were found.					
State regulations					
Massachusetts	: None of	the components are listed.			
New York	: None of	the components are listed.			
New Jersey	: None of	the components are listed.			
Pennsylvania	: None of	the components are listed.			
California Prop. 65 Clear	and Reasonal	<u>ole Warnings (2018)</u>			
Date of issue/Date of revision	: 10/6/2022	Date of previous issue	: 11/18/2021	Version : 7	9/11

### Section 15. Regulatory information

**WARNING**: This product can expose you to chemicals including cumene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	%	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
cumene	<0.01	Yes.	No.	-	-
ethylbenzene	<0.01	Yes.	No.	Yes.	-
naphthalene	<0.001	Yes.	No.	Yes.	-

#### International regulations

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **Inventory list**

United States	: All components are listed or exempted.
Australia	: All components are listed or exempted.
Canada	: All components are listed or exempted.
China	: All components are listed or exempted.
Europe	: All components are listed or exempted.
Japan	: Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.
Malaysia	: Not determined
New Zealand	: All components are listed or exempted.
Philippines	: All components are listed or exempted.
Republic of Korea	: All components are listed or exempted.
Taiwan	: Not determined.
Thailand	: Not determined.
Turkey	: Not determined.
Viet Nam	: Not determined.

### Section 16. Other information

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

#### Procedure used to derive the classification

Classification				Justification		
Not classified.						
History						
Date of issue/Date of revision	: 10/6/2022	Date of previous issue	: 11/18/2021	Version	:7	10/11

### Section 16. Other information

Date of printing	: 10/6/2022
Date of issue/Date of revision	: 10/6/2022
Date of previous issue	: 11/18/2021
Version	: 7
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
References	: Not available.

Indicates information that has changed from previously issued version.

### Notice to reader

THE INFORMATION IN THIS SAFETY DATA SHEET (SDS) WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS OR ACCURACY. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS SDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS SDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE OR APPLICATION.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND/OR DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

CITGO is a registered trademark of CITGO Petroleum Corporation