



CITGO® HyDurance® AW CP Fluid

OVERVIEW




- A premium multi-grade, anti-wear hydraulic fluid designed for applications where dielectric (insulating) properties are required.
- Offers wide temperature range service in mobile hydraulic equipment, particularly in low-temperature conditions where excellent cold startup hydraulic system performance is required.

FEATURES & BENEFITS




- Provides excellent service in equipment used under a wide range of operating conditions and where hydraulic system response is critical.
- High dielectric strength.
- Superior low-temperature flow and pumpability.
- Fluid film strength for warmer climates.
- Excellent anti-wear properties.
- Foam-resistant and separates water readily.
- Protects against rust and corrosion.
- Long service life.
- Excellent viscosity shear stability.



- Recommended for most outdoor and/or mobile hydraulic equipment requiring a fluid with high dielectric strength properties such as cherry picker lift applications, including:
 - Tree trimming, fruit picking mobile equipment
 - Firefighting lift trucks, buckets, etc.
 - Aerial lift buckets
 - Mobile hydraulic systems
 - Garbage collection equipment
 - Public utility vehicles
 - Construction equipment in colder services
- Meets or exceeds the following:
 - Dielectric Strength, ASTM D877, 35 KV minimum
 - ASTM D6158 HM
 - Parker Denison HF-0
 - DIN 51524-2
 - Eaton Brochure 03-401-2010
 - General Motors LS-2
 - JCMAS HK P041
 - ISO 11158 HM
 - SEB 181 222

• **DIELECTRIC STRENGTH RATED**
• **WIDE TEMPERATURE PERFORMANCE**

PROPERTIES**Typical Properties for CITGO HyDurance AW CP Fluid:**

Material Code	633623001
Gravity, ASTM D4052, °API	30.8
Density, lb/gal	7.26
Flash Point, COC, ASTM D92, °F (°C)	367 (186)
Color	Blue-green
Viscosity ASTM D445 D2983:	
cSt at -40°C	20,450
cSt at -23°C	1,590
cSt at -18°C	860
Viscosity ASTM D455:	
cSt at 40°C	25.6
cSt at 100°C	5.4
Viscosity Index, ASTM D2270	155
Pour Point ASTM D97, °F (°C)	-54 (-48)
Oxidation Test ASTM D943, hrs	2775
Rust Test ASTM D665, A and B	Pass
Water Separability, ASTM D1401, at 130°F (54°C)	40-40-0 (10)
Dielectric Strength, ASTM D877, KV, minimum	35

CITGO and HyDurance are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.

Dielectric strength is extremely sensitive to humidity and contamination. Once the containers are opened, the dielectric strength cannot be expected to remain at its original value. Containers should be kept tightly sealed and stored in a dry environment. Dielectric strength rating shown in the above Typical Properties table does not apply to bulk shipments and is only applicable to containers packaged at CITGO packaging facilities.