

# Mystik® SX-7000®

## Synthetic Gear Lubricants

### OVERVIEW




- Heavy duty, state-of-the-art premium synthetic lubricants approved by the Eaton/Fuller Corporation and Rockwell for use in conjunction with their extended warranty programs.
- With up to 500,000 miles of useful life, these premium quality lubricants save the cost and inconvenience of frequent transmission and drive axle lube changes. That's ten times longer service in transmissions (50,000 miles normal) and two and a half times longer service in drive axles (100,000 miles normal) than using conventional petroleum-based lubricants.
- Exceptional proven service in Spicer/Dana transmissions and differentials.
- More horsepower and improved fuel mileage can be achieved as a result of superior lubricating properties.

### FEATURES & BENEFITS



- Meet API Service MT-1 performance requirements for use in non-synchronized manual transmissions used in buses and heavy-duty trucks.
- Superior performance at extreme temperatures and maximum component protection for the extended long haul.
- High- and low-temperature performance and long-term thermal, oxidation, and shear stability (resistance to viscosity loss in service) far superior to conventional transmission and drive axle lubricants.
- Improved lubrication at start-up, easier shifting and less gear wear in low temperature environments.
- All-climate, year-round performance, including superior low-temperature performance with extremely low channel points.
- Improved component protection to reduce wear.
- Longer drive axle and lubricant life.
- Extended seal life.
- Good foam control and excellent demulsibility.
- Improved fuel economy and horsepower.

### APPLICATIONS



#### Product Name

SX-7000 75W-90  
SX-7000 80W-140

#### Description


Synthetic SAE 75W-90  
Synthetic SAE 80W-140

#### Use

EP-Drive Axle/Transmission  
EP Drive Axle


#### Mystik SX-7000 Synthetic Gear Lubricants 75W-90 and 80W-140:

- API GL-5.
- Specially formulated for extended drain and severe service in heavy duty drive axles.

**APPLICATIONS**

**NOTE:** Mystik SX-7000 75W-90 and 80W-140 meet or exceed all applicable performance requirements for API Gear Lubricant Classification GL-5 and MT-1.

- SAE J2360
- Dana SHAES 429
- Detroit Diesel DFS 93K219.01 (75W-90)
- Dana SHAES 256revE (75W-90)
- Navistar MPAPS B-6821
- Meritor O-76N (75W-90), O-76B (80W-140)
- Mack GO-J (80W-140)
- Mack GO-J Plus (75W-90)
- International TMS-6816

**PROPERTIES****Typical Properties for Mystik SX-7000 Synthetic Gear Lubricants:**

Material Code	663750002	663751002
SAE Viscosity Grade (J306-8)	75W-90	80W-140
AGMA Grade (ASTM D2422)	4 EP	5-6 EP
Gravity, ASTM D4052, °API	33.5	32.0
Specific Gravity at 60°F	0.91	0.92
Density, lb/gal at 60°F	7.15	7.25
Viscosities:		
at -26°C, cP	—	90,000
at -40°C, cP	125,000	—
at 40°C, cSt.	120	310
at 100°C, cSt.	15.9	31.2
Viscosity Index	140	139
Pour Point, ASTM D97, °F (°C)	-48 (-54)	-33 (-36)
Channel Point, FTMS 3456, °F (°C)	-60 (-51)	-55 (-48)
Flash Point, ASTM D92, °F (°C)	400 (205)	410 (210)
Foam Test, ASTM D892, Sequence I, II, III	Pass	Pass
Copper Strip Corrosion, ASTM D130 3 hrs. at 250°F	Pass	Pass
Thermal Stability Test	Pass	Pass
Demulsibility Test	Pass	Pass
Timken OK Load, ASTM D2782, lb	50	85
Four-Ball EP Weld Point, ASTM D2783, kgf	—	400
Four-Ball Load Wear Index, ASTM D2783, kgf	—	63.8
Color	1.5	1.5

©2019 CITGO Petroleum Corporation

The Mystik Lubricants name, logo and all related marks are registered trademarks protected by federal law. All other registered trademarks or trademarks are the property of their respective owners.